


LAS3003 SI DOOR BOTTOM SEAL

FITTING GUIDE



LENGTH _____

CONTENTS

- LAS3003 si door bottom seal
- Bag of screws

TOOLS REQUIRED

- Pencil or marker
- Knife
- Saw, hand or power
- Drill, hand or power
- Screwdriver
- Router

FACE-FIXED OR SEMI-REBATED

STEP 1

If installed, remove door from its hinges, lay door on its edge and firmly restrain.

STEP 2

Measure and mark out the seal position along the centre line of the door stile/ bottom. Note that the finished groove should be 20mm wide.

STEP 3

Fit a suitable cutter into the router, set guide and machine a 5mm deep groove along the edge/bottom of the door.

STEP 4

Clean dust and chips from the groove and check depth by applying seal.

STEP 5

Measure the door height/width and cut the seal to suit, using a sharp knife for the silicone gasket and a saw for the aluminium section.

STEP 6

Replace the silicone gasket and screw fix the aluminium section into the groove using the screws supplied (fixing holes are pre-drilled).

STEP 7

Ends of the aluminium channel may be centre punched to prevent gasket movement.

NOTE

We recommend the LAS3003 si is used together with a Lorient threshold plate.

NOTE

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to ensure the door assembly to which it is fitted, closes and latches properly.

NOTE

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.



V2



Lorient Polyproducts Ltd
Endeavour House
Fairfax Road
Heathfield Ind Estate
Newton Abbot
Devon TQ12 6UD
United Kingdom

+44 (0)1626 834252
www.lorientgroup.com

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Limited.
© Lorient Polyproducts Ltd 2019

For more information please call:

+44 (0)1626 834252