


LAS3005 DOOR BOTTOM SEAL

FITTING GUIDE



LENGTH _____

CONTENTS

- LAS3005 door bottom seal

TOOLS REQUIRED

- Tape measure
- Pencil or marker
- Router with 4mm cutter
- Scissors, knife or snips

NOTE

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

INSTALLATION DETAIL

STEP 1

Remove the seal from the packaging and measure the door width to determine the seal length required. Cut length to suit door bottom.

STEP 2

Groove the door bottom 4mm wide x 6mm deep.

STEP 3

Push fit the LAS3005 product into the groove.

NOTE

Do not install this product to impede the opening or closing of the door. It is recommended to check the adjustment of the door seal periodically to insure the door assembly closes and latches properly, whether or not equipped with a closing device.



For more information please call:

+44 (0)1626 834252

V1



Lorient Polyproducts Ltd
Endeavour House
Fairfax Road
Heathfield Ind Estate
Newton Abbot
Devon TQ12 6UD
United Kingdom

+44 (0)1626 834252
www.lorientgroup.com

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Limited.
© Lorient Polyproducts Ltd 2019