


LAS7004 SI PERIMETER SEAL

FITTING GUIDE

certifire
(CF5179)



LENGTH _____

CONTENTS

- LAS7004 si perimeter seal
- Bag of screws

TOOLS REQUIRED

- Tape measure
- Saw, power or hand
- Screw driver
- 2mm drill bit
- Drill, power or hand
- Knife
- Pencil or marker
- Router (rebated installation)

NOTE

It is not necessary to remove the door from its hinges, unless otherwise specified.

FACE-FIXED TO MEETING STILES

STEP 1

Remove the seal from the packaging and measure the height of the meeting stile.

STEP 2

Pull back the silicone gasket and cut the aluminium carrier to required length.

STEP 3

Slide silicone gasket back and cut the gasket to the required length.

STEP 4

Position the carrier against the meeting stile of the active leaf and mark out the hole locations with a pencil.

STEP 5

Drill pilot holes with a 2.0mm drill bit (if required).

STEP 6

Screw fix the aluminium carrier length to the meeting stile using the screws supplied.

STEP 7

Centre punch top corners of aluminium channel to prevent the gasket from "creeping".

STEP 8

Close the door and ensure the seal makes uniform contact with the opposite door leaf.

REBATE INSTALLATION DETAIL

STEP A


Remove the active door leaf (which opens first) from its hinges.

STEP B

Using a router, rebate a 16mm wide x 3mm deep groove to the stile of the active leaf.

STEP C

Re-hang the door and follow steps 1-9 of the instructions.



NOTE

Ensure that the installation of this product does not impede the opening or closing of the door. It is recommended to check the door seal periodically to ensure the door assembly to which it is fitted, closes and latches properly.

We recommend that the LAS7004 si perimeter seal is fitted with a drop seal.

NOTE

Recommendations as to methods, use of materials and construction details are based on the experience and knowledge of Lorient and are given in good faith as a general guide and service to designers, contractors and manufacturers.

Lorient reserves the right to make alterations or delete any installation detail without prior notice.

V2



Lorient Polyproducts Ltd
Endeavour House
Fairfax Road
Heathfield Ind Estate
Newton Abbot
Devon TQ12 6UD
United Kingdom

+44 (0)1626 834252
www.lorientgroup.com

All rights reserved. No part of this fitting guide may be reproduced, stored in a retrieval system, or transmitted in any means, electronic, mechanical, photocopying, recording or otherwise without the written permission of Lorient Polyproducts Limited.
© Lorient Polyproducts Ltd 2019